LED, FS-技术 QC 固定夹, 28.8 V, 绿色, LED











描述

- > 夹子带SMT LED
- > 发光按钮开关,发光选择开关,可发光急停按钮和发光附件的照明
- > 安装: 锁定触点模块QC和用于发光附件的夹架
- > 使用带光导体的触点模块发光效果更佳
- ▶ 若要明亮色彩,我们建议在灯罩颜色中选择LED的颜色

技术参数

> 一般

发光元件颜色 绿色 -40 °C 工作温度,最低 工作温度,最高 85 °C 可发光 是 发光元件 LED 包装数量 10 碎片

MOQ 秩序 10 碎片 RoHS 一致性 REACH 一致性 是

> 机械特性

净重

背面端子 快插端子2.8 x 0.8

> 电气特性

数: 1/1

发光元件工作电压, 最低 19.2 V 发光元件的工作电压,最大 28.8 V 电压型 DC

额定工作电压 19,2-28,8 V 功率损失 0.058 Watt

4006-022-002

直接链接

> RAFI eCatalog

The information in this data sheet only contains general descriptions and / or performance features, which may not apply precisely as described to the respective application, and which my change due to further product enhancements. The technical data, illustrations and other information about our products are the mere results of individual technical testing. These descriptions and other product features are only binding if they expressly agreed upon at the time of the conclusion of a binding contract. In all other cases, we reserve the right to make technical changes as well as changes of availability. Pictures and other graphic illustrations are approximations only. All product names may be trademarks or brand names of the RAFI Group or any other sub-supplier of RAFI. The use of such by any third parties for their own purposes may infringe the rights of the respective entity holding those rights. 版本: 2021年12月10日 页

1 公克

RAFI GmbH & Co. KG

Ravensburger Str. 128-134 88276 Berg / Ravensburg Germany www.rafi-group.com info.headquarters@rafi-group.com